



Southeastern Aluminum Products

904-781-8200 • P.O. Box 6427, Jacksonville, FL 32236 • www.SoutheasternAluminum.com

SIGNATURE HINGE

Specifications and Features

Series 100, 200 and 200A

- Solid forged brass construction
- Designed for 3/8" (10 mm) and 1/2" (12mm) glass-to-wall mount and glass-to-glass mount
- Wall-mount hinges are available in both H-back and offset styles
- The H-back style has a refined bevel allowing you to install the glass as close to the wall as you desire
- Cycle testing performed under an actual glass load revealed that typical return hinge springs break near 6000 cycles. Our upgraded tool steel return springs ensured flawless function even after 38,000 cycles, the equivalent of 26 years of use
- Waffled plates with integrated ridges ensure positive glass grip, eliminate gasket creep, and prevent hinge plates from loosening over time
- Option of Allen or Phillips head stainless steel clamp screws for face plates
- ORB color matches all extrusions, handles, and hardware
- Uses same glass cut-out as CRL Pinnacle and Cologne hinges
- Best in industry adjustable hinge decreases installation time and ensures installers have the best hardware for one trip installations. Fine tune the door-to-panel glass alignment and never shim behind a wall plate again. Perfect centering even after being tested under load for 48,000 cycles, the equivalent of 33 years of use. This product is quickly becoming the standard hinge for the shower door installation professional
- On the series 200 and 200A heavy duty hinges the steel pins are removable to allow a rectangular shaped cutout with increased adjustability
- The series 200 has a reversible pivot pin to allow a 5° offset for tighter closure
- Self-closing from 15°

Maximum Capacities and Door Widths:			
SERIES	NO. OF HINGES	WEIGHT	DOOR WIDTH
100	2	80	28"
	3	120	32"
200/200A	2	110	36"
	3	140	36"



Southeastern Aluminum Products

904-781-8200 • P.O. Box 6427, Jacksonville, FL 32236 • www.SoutheasternAluminum.com

SIGNATURE HINGE

Specifications and Features

Series 300 and 400A

- Solid forged brass construction
- Designed for 3/8" (10 mm) and 1/2" (12mm) glass-to-wall mount and glass-to-glass mount
- Wall-mount hinges are standard with full back-plate.
- Cycle testing performed under an actual glass load revealed that typical return hinge springs break near 6000 cycles. Our upgraded tool steel return springs ensured flawless function even after 38,000 cycles, the equivalent of 26 years of use
- Waffled plates with integrated ridges ensure positive glass grip, eliminate gasket creep, and prevent hinge plates from loosening over time
- Option of Allen or Phillips head stainless steel clamp screws for face plates
- ORB color matches all extrusions, handles, and hardware
- Uses same glass cut-out as CRL Pinnacle and Cologne hinges
- Best in industry adjustable hinge decreases installation time and ensures installers have the best hardware for one trip installations. Fine tune the door-to-panel glass alignment and never shim behind a wall plate again. Perfect centering even after being tested under load for 48,000 cycles, the equivalent of 33 years of use. This product is quickly becoming the standard hinge for the shower door installation professional
- On the series 400A heavy duty hinges the steel pins are removable to allow a rectangular shaped cutout with increased adjustability
- The series 400A is fully adjustable to allow for angled walls and offset to any degree desired.
- Self-closing from 15°

Maximum Capacities and Door Widths:

SERIES	NO. OF HINGES	WEIGHT	DOOR WIDTH
300	2	80	28"
	3	120	32"
400A	2	110	36"
	3	140	36"



Southeastern Aluminum Products

904-781-8200 • P.O. Box 6427, Jacksonville, FL 32236 • www.SoutheasternAluminum.com

SIGNATURE HINGE

Specifications and Features

Series 500 Pivot Hinge

- Solid forged brass construction
- Designed for 5/16" (8 mm) and 3/8" (10 mm) glass
- Easy-adjust header application requiring no-hole drilling
- Reversible wall mount feature
- Self-closing from 15°
- Option of Allen or Phillips head stainless steel clamp screws for face plates
- Uses same glass cut-out as CRL Prima pivot hinge
- ORB color matches all extrusions, handles, and hardware
- Maximum capacity of 110 lbs and a maximum door of 31"